



DZ-460/2G Floor Type Vacuum Packaging Machine is using microcomputer control system, which with reasonable structure, stably performance, widely application, and convenience maintenance. The lid is made of high-quality acrylic material which is solid and transparent for observing the packing situation within the vacuum chamber at any time. Machine with high automatic degree, which the vacuuming, sealing and cooling will be automatic operation after close the lid.

Features:

1. Microcomputer control system which is used for precise and stable setting vacuuming and sealing time according to different packing material and packing requirement, easily for operation.
2. The lid is made of high-quality acrylic material which is solid and transparent for observing the packing situation within the vacuum chamber at any time.
3. Machine equipped with high efficiency vacuum pump, lower noise, big capacity and working stably.
4. The main structure of the machine is made of #304 stainless steel, which ensures its elegant appearance as well as the anticorrosion in harsh caustic environment.
5. The “V” shaped chamber lid gasket made of high-density material guarantees the sealing performance of the machine in routine work. The compression and wearing resistance of the material extends the service life of the sealing tape and reduces change frequency.
6. The heavy-duty casters (with brake) on the machine features superior load bearing performance so that the user may move the machine with ease.

Model	DZ-460/2G
Machine Dimensions(mm)	790 × 630 × 960
Chamber Dimensions(mm)	720 × 480 × 210 (150)
Sealer Dimensions(mm)	460 × 8 × 2
Vacuum Pump(m ³ /h)	20
Power Consumption(kw)	0.9
Electrical Requirement(v/Hz)	220/50
Production Cycle(times/min)	1-2
Net Weight(kg)	119
Shipping Dimensions(mm)	910 × 760 × 1030

